

AccuLux HL 25 EX



Knickkopf-Handleuchte

EX-geschützte LED-Knickkopf-leuchte, in Fahrzeugen oder Gebäuden montierbar.



Flexible-head safety lamp

EX-proof LED flexible-head lamp, for installation in vehicles or buildings.

Merkmale:

- Entspricht der Deutschen Feuerwehnorm DIN 14649
- ATEX-zertifiziert
- EX-geschützte Zonen 1, 2, 21, 22 (alle Gase + Stäube)
- Lithium-Ionen-Akku (3,7 V / 5,0 Ah)
- Gesichert gegen Tiefentladung
- LCD-Kapazitätsanzeige
- Mit Notlichtfunktion (230 V) (schaltet sich bei Stromausfall ein)
- 3 Schaltstufen: 2 Leuchtstufen + Blinkmodus
- Schutzart: IP 67
- Stoßfest, staubdicht und tauchfähig bis 1 m
- Gehäusematerial nicht brennbarer Kunststoff
- Leuchtdauer: ca. 5 h / 10 h
- Ladezeit: ca. 6 h
- Leuchtenkopf in 90°, 120°, 150°, 180° rastbar
- Gewicht ca. 540 g
- Befestigungsklammer mit Ringöse
- Lichtstrom: ca. 170 Lumen
- Leuchtweite: ca. 200 m

Features:

- Complies with the german fire service standard DIN 14649
- ATEX certified
- EX-proof zones 1, 2, 21, 22 (all gases + dusts)
- Lithium-Ion-Accu (3,7 V / 5,0 Ah)
- Protection against total discharge
- LCD capacity indicator
- With emergency light function (230 V) (turns on in case of power failure)
- 3 step switch: 2 steps for brightness + flash function
- Protection class: IP 67
- Impact-resistant, dust-proof and submersible up to 1 m
- Casing material non flammable plastic
- Operating time: ca. 5 h / 10 h
- Charging time: ca. 6 h
- Swivelling lamp head at 90°, 120°, 150°, 180°
- Weight ca. 540 g
- Clamp unit with ring loop
- Lum. flux: ca. 170 lumes
- Range: ca. 200 m



Akkuleuchte

Acculamp

Art.Nr. 458481s



Akku Set mit Ladestation
12-24 V

Accu set with charging
station 12-24 V

Art.Nr. 458581s



Akku Set mit Ladestation
12-24 V + 230 V

Accu set with charging
station 12-24 V + 230 V

Art.Nr. 458591



Ladestation L25 1-fach bis 5-fach
für 12-24 V oder 230 V

Charging station L25 1-fold to
5-fold for 12-24 V or 230 V

Art.Nr. 458861 – 458865 (12-24 V)
Art.Nr. 458871 – 458875 (230 V)